



KEY FEATURES

- Powered by phantom power from amplifier.
- With red ring indicator for service.
- XLR convenient connector.
- High sensitivity flexible gooseneck.
- Unidirectional condenser microphone.
- Built-in low frequency attenuator.

SPECIFICATION

STARVIEW G-410-C MICRO SPECIFICATIONS

Model	G-410-C
Type	Unidirectional
Frequency Response	50Hz ~ 18KHz
Max Sound Pressure	120dB (at 1KHz ≤ 1%T.H.D)
Input Sensitivity	200Ω ± 30%
Sensitivity	-47dB ± 3dB (0dB = 1V/Pa at 1KHz)
S/N Ratio	68dB
Power Supply	Phantom Power 48V
Mic Length	375 mm
Output Connector	Balanced XLR connector
Cable Length	3 Meters
Weight	0.88Kg

Corporate offices

STARVIEW TECHNOLOGIES PTE LTD
Singapore Headquarters
60 Kaki Bukit Place
#05-19 Eunos Techpark
Singapore 415979

Tel: +65 3157 5338
Fax: +65 3112 8181

Worldwide offices

STARVIEW TECHNOLOGIES VIETNAM
Hanoi Office
R9, 33th Floor, C2 Building, D'Capitale,
119 Tran Duy Hung Street,
Trung Hoa – Cau Giay, Hanoi
Ho Chi Minh Office
#C9-16, Block A, Sky Center Building,
#10 Pho Quang Street,
Tan Binh District, Ho Chi Minh City

Tel: (024) 66661268
Hotline: 19008695
Sale Contact: 0866.207.855

Representatives

Brazil
Tel: +55 11 9-8244-7630

Germany
Tel: +49 172 946 69 39

France - Benelux - Africa
Tel: +33 782 702 214

**Southern, Eastern Europe
& Middle East Operations**
Tel: +420 602 66 75 66

