



FEATURES

- Professional compact mixer with ultra-low noise discrete microphone preamplifier and +48V phantom power, powerful, full-featured and mellifluous audio quality.
- Provide 4 channels of Mic input interface compatible with 4 line input interfaces, microphone input interface with 48V phantom power.
- Provide 4 sets of stereo linear input, which can be connected to stereo equipment.
- Each channel of the mono input channel has a 3-band EQ with a peak LED indicator.
- Provide 1 set of stereo main output, 1 set of auxiliary output, one set of stereo monitor output, 1 channel headphone monitor output, 1 set of CD/Tape output.
- Built-in 24-bit DSP effects, providing 100 preset effects.

SPECIFICATION

STARVIEW M12-FX-C SPECIFICATIONS	
Model	M12-FX-C
Microphone Input	4 channels (4 XLR)
Line Input	4-channel single plug mono/stereo automatic switching hybrid interface
Stereo Input	4 sets (8 channels mono)
CD/Tape Input	1-channel CD/TAPE RCA stereo input interface
Output Channel	1 stereo main output, 1 auxiliary output, 1 stereo monitor output, 1 earphone monitor output, 1 CD/Tape output
Effect	Effects: 24-bit DSP effects (including vocals, small houses, halls, echoes, echoes + reverbs, plates, vocals, chorus GTR, rotating GTR, vibrato GTR type), 100 preset effects

Website: www.starviewtech.asia or www.starviewtech.net | Email: sales@starviewint.com | Tell: +65 31575338

Phantom Power	+48V with switch
Frequency Response	20Hz to 50KHz (0, -1dB); 20Hz to 130KHz (0, -3dB)
THD	<0.003% (A-weighted)
Microphone Balanced Input Noise	-119dB (A-weighted)
Common Mode Rejection Ratio	60dB
Single Channel Input Gain	MIC: 0 to 48dB, LINE: -33 to +15dB
Stereo Channel Input Gain	LINE: -8 to +6dB
Main Mix Crosstalk	-87dBu (A-weighted)
Channel Crosstalk	-85dBu (A-weighted)
Maximum Output Level	+20dBu
MIC Input High-pass Filtering	75Hz, 18dB/oct
Single Channel Equalization	High frequency: ±15dB@12KHz; medium frequency: ±12dB@2.5KHz; low frequency: ±15dB@80Hz
Power Supply	External 18AC (AC 230-240V 50/60Hz) power adapter
Power Consumption	≤18W
Dimension (L x W x H)	271 x 259 x 54.3mm
Weight	1.9Kg

Corporate offices

STARVIEW TECHNOLOGIES PTE LTD
Singapore Headquarters
60 Kaki Bukit Place
#05-19 Eunos Techpark
Singapore 415979

Tel: +65 3157 5338
Fax: +65 3112 8181

Worldwide offices

STARVIEW TECHNOLOGIES VIETNAM
Hanoi Office
R9, 33th Floor, C2 Building, D'Capitale,
119 Tran Duy Hung Street,
Trung Hoa – Cau Giay, Hanoi
Ho Chi Minh Office
#C9-16, Block A, Sky Center Building,
#10 Pho Quang Street,
Tan Binh District, Ho Chi Minh City

Tel: (024) 66661268
Hotline: 19008695
Sale Contact: 0866.207.855

Representatives

Brazil
Tel: +55 11 9-8244-7630

Germany
Tel: +49 172 946 69 39

France - Benelux - Africa
Tel: +33 782 702 214

**Southern, Eastern Europe
& Middle East Operations**
Tel: +420 602 66 75 66

