



## KEY FEATURES

- Industrial modeling steel panel, professional design and durable surface, anti-dust mesh panel with folding structure design, removable cleaning cooling vents.
- Power on soft-start, to prevent absorbing a large current of the power grid, from interference with other electrical equipment.
- Intelligent control forced cooling design, low fan noise, high cooling efficiency etc.
- Built-in intelligent limiter system, control the power module and the speaker system work in a safe range.
- Built-in 30Hz / 50Hz high-pass filter.
- Multiple modes: stereo, bridge, parallel.
- Abundant reserve power, with 2R low-impedance output, high-fidelity and perfect sound quality.
- High quality transformer, low resistance and large capacity electrolytic filter, ensure large dynamic work smoothly.
- Class-H efficient power amplifier, comprehensive and reliable security protection measures and working status indicator (short circuit, overload, DC and overheating protection, transformer overheating protection), let users at easy use.

## SPECIFICATION

STARVIEW PA2-700-C, PA2-1200-C SPECIFICATIONS		
Model	PA2-700-C	PA2-1200-C
Stereo/ Parallel 8Ω X 2	700W x 2	1200W x 2
Stereo/ Parallel 4Ω X 2	1050W x 2	1800W x 2
Stereo/ Parallel 2Ω X 2	1500W	2700W
Bridged 8Ω	2100W x 2	3600W
Bridged 4Ω	3000W x 2	5400W
Integrated Socket	XLR, TRS interface	XLR, TRS interface

Website: [www.starviewtech.asia](http://www.starviewtech.asia) or [www.starviewtech.net](http://www.starviewtech.net) | Email: [sales@starviewint.com](mailto:sales@starviewint.com) | Tell: +65 31575338

Voltage Gain (@1KHz)	37.7 dB	40 dB
Input Sensitivity	0dBu(1V)	0dBu(1V)
Input Impedance	10KΩ Unbalance, 20KΩ balance	10KΩ Unbalance, 20KΩ balance
Frequency Response (@1W Power)	20-20KHz/±1dB	20-20KHz/±1dB
THD+N	≤0.05%	≤0.05%
S/N Ratio (A Weighting)	≥100d	≥100d
Damping (@ 1KHz)	≥300@ 8Ω	≥300@ 8Ω
Resolution (@1KHz)	≥80dB	≥80dB
Protection Mode	Over-current protection, DC protection, short circuit protection	Over-current protection, DC protection, short circuit protection
Indicator	Power, protection, distortion	Power, protection, distortion
Cooling Method	Fan cooling	Fan cooling
Power Supply	~220 - 240V 50/60Hz	~220 - 240V 50/60Hz
Maximum Power Consumption	4500W	8000W
Dimensions (L x W x H)	483 x 88 x 494mm	483 x 524 x 132mm
Weight	19.6Kg	32Kg

Corporate offices

STARVIEW TECHNOLOGIES PTE LTD  
**Singapore Headquarters**  
 60 Kaki Bukit Place  
 #05-19 Eunos Techpark  
 Singapore 415979

Tel: +65 3157 5338  
 Fax: +65 3112 8181

Worldwide offices

STARVIEW TECHNOLOGIES VIETNAM  
**Hanoi Office**  
 R9, 33th Floor, C2 Building, D'Capitale,  
 119 Tran Duy Hung Street,  
 Trung Hoa – Cau Giay, Hanoi  
**Ho Chi Minh Office**  
 #C9-16, Block A, Sky Center Building,  
 #10 Pho Quang Street,  
 Tan Binh District, Ho Chi Minh City

Tel: (024) 66661268  
 Hotline: 19008695  
 Sale Contact: 0866.207.855

Representatives

**Brazil**  
 Tel: +55 11 9-8244-7630

**Germany**  
 Tel: +49 172 946 69 39

**France - Benelux - Africa**  
 Tel: +33 782 702 214

**Southern, Eastern Europe & Middle East Operations**  
 Tel: +420 602 66 75 66

