



FEATURES

- Single display dual channel.
- The receiver uses advanced PLL phase-locked loop and microcomputer CPU control system and is compatible with manual frequency selection and automatic infrared frequency locking.
- The receiver system adopts high performance speech companding technology to provide perfect sound quality.
- Support 6 sets of 12 frequencies being used at the same zone without interference with each other.
- Applicable to classrooms and conference rooms, etc.

SPECIFICATION

SYSTEM SPECIFICATIONS	
Frequency Range	640 - 690 MHz
Oscillation Mode	Phase-locked loop frequency synthesis (PLL)
Number of Channel	200
Frequency Response	50-15KHz (±2dB)
Working Distance	50m on open space
Frequency Interval	250 KHz
Carrier Wave Stability	±10PPm ≤ 10KHz
Image Interference Ratio	>80dB
SNR	>105dB (1KHz-A)
Sensitivity	-105dBm (12dB S/N AD)
THD	0.5% (ref. ±40KHz deviation. 1KHz tone)
Muted Method	Muted and sound code locked loop

Website: www.starviewtech.asia or www.starviewtech.net | Email: sales@starviewint.com | Tell: +65 31575338

RECEIVER SPECIFICATIONS

Display	LCD display
Working Temperature	-10°C + 60°C (not battery operating temperature)
Case	Galvanized cold-rolled plate
Audio Output Level	Unbalanced 600Ω, load -2 dBV
Output Impedance	Unbalanced 600Ω
Unbalanced Output	TRS 6.35mm connector
Power Supply	DC 12V - 1A
Dimension (L x W x H)	420 x 180 x 41 mm
Weight	1.48 Kg (excluding antenna)

MICROPHONE SPECIFICATIONS

Frequency Range	640 - 690 MHz
Output Power	High power 30mW
Harmonic Radiation	< -55dBc
Maximum Deviation	± 70KHz
Maximum Input Sound Pressure	140dB SPL
Oscillation Mode	FM PLL frequency synthesis
Frequency Adjustment	Automatic locking and manual adjustment of receiver working channels
Battery	2 AA 1.5V batteries
Weight	0.32Kg(hand-held), 0.04Kg(lapel),(excluding battery)
Dimension	249(L) x 35(D) (hand-held), 109(L) x 64.3(W) x 21(H) (lapel)

Corporate offices

STARVIEW TECHNOLOGIES PTE LTD
 Singapore Headquarters
 60 Kaki Bukit Place
 #05-19 Eunos Techpark
 Singapore 415979

Tel: +65 3157 5338
 Fax: +65 3112 8181

Worldwide offices

STARVIEW TECHNOLOGIES VIETNAM
Hanoi Office
 R9, 33th Floor, C2 Building, D'Capitale,
 119 Tran Duy Hung Street,
 Trung Hoa – Cau Giay, Hanoi
Ho Chi Minh Office
 #C9-16, Block A, Sky Center Building,
 #10 Pho Quang Street,
 Tan Binh District, Ho Chi Minh City

Tel: (024) 66661268
 Hotline: 19008695
 Sale Contact: 0866.207.855

Representatives

Brazil
 Tel: +55 11 9-8244-7630

Germany
 Tel: +49 172 946 69 39

France - Benelux - Africa
 Tel: +33 782 702 214

**Southern, Eastern Europe
 & Middle East Operations**
 Tel: +420 602 66 75 66

